



# PRODUCT DATA SHEET

## WALL AND CEILING CLADDING

### STORMGRIP

#### ABOUT STORMGRIP

A solvent-free adhesive suitable for use with all STORM PVC cladding materials.

STORMGRIP is a two-part polyurethane, general purpose, weather resistant, gap filling adhesive suitable for bonding a wide range of construction materials in both interior and exterior applications. It is ideal for use with our hygiene cladding range.



#### PHYSICAL DATA

PHYSICAL DATA	REQUIREMENTS
Base	Polyurethane
Viscosity at 20 °C	Part A: Paste approximately 3850 poise Part B: Low viscosity liquid
Specific Gravity at 20 °C	Part A: 1.70 - 1.73 Part B: 1.21 - 1.23
Chemical Resistance	Resistant to water, dilute acids and alkalis and aliphatic oils
Solvents	None
Flammability	N/A
Service Temperature	-40 °C to 130 °C
Application Temperature	Minimum 10 °C Maximum 30 °C
Storage Life at 25 °C	6 months in unopened containers, store between 5 °C and 25 °C
Cover for Cladding Walls with PVC Sheeting	1 x 6.5 kg tub per 1220 mm by 2440 mm sheet

#### IMPORTANT NOTICE

Data contained in this document is for information only and is believed to be reliable. Southgate Plastics Ltd cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine the suitability of the product for any specific purpose. We are pleased to provide a sample upon request.

Before using this product, ensure that you have been supplied with and have read the following information: the hazard label (complying with the latest CDG/CPL regulations) applied to the container and Material Safety Data Sheets, Part A and Part B.

