



PRODUCT DATA SHEET

WALL AND CEILING CLADDING

STORMGRIP

ABOUT STORMGRIP

A solvent-free adhesive suitable for use with all STORM PVC cladding materials.

STORMGRIP is a two-part polyurethane, general purpose, weather resistant, gap filling adhesive suitable for bonding a wide range of construction materials in both interior and exterior applications. It is ideal for use with our hygiene cladding range.



PHYSICAL DATA

PHYSICAL DATA	REQUIREMENTS
Base	Polyurethane
Gel time (100g @ 250C):	30-40 minutes
Tack Free Time	4-6 hours
Full Cure	24 Hours
Recommended application temp (substrates):	Minimum 15°C
Recommended application temp (enviroment):	Minimum 10°C

IMPORTANT NOTICE

Data contained in this document is for information only and is believed to be reliable. Southgate Plastics Ltd cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine the suitability of the product for any specific purpose. We are pleased to provide a sample upon request.

Before using this product, ensure that you have been supplied with and have read the following information: the hazard label (complying with the latest CDG/CPL regulations) applied to the container and Material Safety Data Sheets, Part A and Part B.





PRODUCT DATA SHEET

WALL AND CEILING CLADDING

STORMGRIP

PREPARATION & APPLICATION

Ensure that the surfaces to be bonded are smooth, clean and free from dust or other deposits. Most construction grade materials are suitable such as wood, concrete, brick, insulation materials, porous and non-porous.

Pour the contents of Part B container into the Part A container and mix thoroughly. A mechanical mixer gives the best mixing results.

Apply the mixed adhesive to the substrate by means of a scraper or notched trowel.

Bed the material to be bonded into adhesive and allow to cure. The adhesive quickly sets up sufficiently to hold components in position but full cure will require up to 24 hours.

HANDLING AND STORAGE

Consult Safety Data Sheet prior to use.

Always test STORMGRIP to determine suitability for your particular application prior to use in production SDS must be read and understood before use.

STORMGRIP should be stored in the original cartridges in a cool, dry place, at a temperature range of between 5°C and 25°C. In these conditions it has a storage life of at least 6 months.

IMPORTANT NOTICE

Data contained in this document is for information only and is believed to be reliable. Southgate Plastics Ltd cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine the suitability of the product for any specific purpose. We are pleased to provide a sample upon request.

Before using this product, ensure that you have been supplied with and have read the following information: the hazard label (complying with the latest CDG/CPL regulations) applied to the container and Material Safety Data Sheets, Part A and Part B.

